PLACE ACQUIRED DATE OF INFO. SUPPLEMENT TO REPORT NO. THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION	eclassified	in Pa	art - Sanitized Copy Approved for Release 2012/0			
AMBJECT Torine Reals Squire and Select Installed in NO. OF FAGES 2 SOX1-HUM MACE REQUIRED NO. OF ENGLS NOTE OF NOTE SUPPLEMENT TO SOX1-HUM REPORT NO. THIS IS UNEVALUATED INFORMATION SOX1-HUM SOX1-HUM THIS IS UNEVALUATED INFORMATION 1. The Ministry of Industry has been given the tack of furnishing the new East German fiching fleet and cosm-resing repurations ships with the follow- ing specially-inveloped equipment a. Two-stage transmitter, 20-watt, R/T.4 b. Two-stage transmitter, 24' transmitter for cosm-resing siles and 20-watt which to ship communication, R/T. 2. The two-stage 20-watt transmitter is developed for R/T communication with the new Rant Commun fishing fleet. R has a freenemy of 1.5 to 3.5 ac's non the accompanying receiver is a seven-circuit superdeterodyne. The sumply is 24 volts over two transformers. 3. The two-stage 20-watt transmitter is a W/T and R/T transmitter for nock gover transmissions of about 80 watts. The whole is similar to the one described in pumpruph 2 above except that the receiver has an antitional intermediate frequency oscillator. 4. The shine' transmitter with a peak power of 200 watte has a frequency range of 3-20 mc s. b. The transmitter with a peak power of 200 watte has a frequency range of 3-20 mc s. c. All of this equipment is fed by an AC of 220 volts.			CENTRAL INTELLIGENCE AGEN	CV REPORT		
AND OF ENGLS SOX1-HUM NO. OF ENGLS SUPPLEMENT TO REPORT NO 1. The Ministry of Industry has been given the tack of furniching the new bant German fiching fleet and cocan-going reparations ships with the following specially—involved and the Sound person of the state of the st	4		information repo	DERT ON MO		
Seat German and Soviet Ships NO. OF ENCLS. COTE SLOW SUPPLEMENT TO SEPORI MO. THIS IS UNEVALUATED INFORMATION 1. The Binistry of Industry has been given the tack of furnishing the new East German fishing fleet and cosen-going reparations ships with the following specially-developed equipment 1. Two-stage transmitter, 20-watt, NT.* b. Two-stage transmitter, with 80-watt peak power output, 1:/T* and 8/T. c. 200- and 100-watt NT transmitters for occan-going ships and 20-watt ship to ship consumication, R/T. The two-stage 20-stat transmitter is developed for R/T communication with the new East German fishing fleet. It has a frequency of 1.5 to 3.5 mc's and the accompanying receive is a seven-circuit superheterodyne. The sumply is 2% volts over two transformers. 3. The two-stage 80-stat transmitter is a WT and R/T transmitter for peak power transmissions of about 80 watts. The whole is stillar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The shins' transmitter and ship to ship communications equipment are described as follows: a. The transmitter with a peak power of 200 watto has a frequency range of 3-70 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's + 25 fc's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. 4. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding entouna. e. All of this equipment is fed by an AC of 220 volts.		Cer	rommar (Charache n Tane)	DARE DISTR RO KAR DI		
SUPPLEMENT TO SOX1-HUM SUPPLEMENT TO REPORT MO 1. The Ministry of Industry has been given the task of furnishing the new East German fishing fleet and ocean-going reparations ships with the following specially—isveleped equipment 3. Two-stage transmitter, 20-watt, 8/7,* b. Two-stage transmitter, 20-watt, 8/7,* c. 200- and 100-ast thy Transmitter for coesn-going ships and 20-watt ship to ship communication, 8/7. 2. The two-stage 20-ant transmitter is developed for R/T communication with the new Reat German fishing fleet. It has a frequency of 1.5 to 3.5 m/s and the accompaning receiver is a cover-circuit shape the ship to ship communication. R/T. 3. The two-stage 20-ant transmitter is developed for R/T communication with the new Reat German fishing fleet. It has a frequency of 1.5 to 3.5 m/s and the accompaning receiver is a cover-circuit shapelet advantage to a solution of new 100 watts. The whole is stillar to the one described an approprial of a cover two transmitters. 4. The ship of transmitters and ship to ship communications equipment are Generabed as follows: 1. The transmitter with a peak power of 200 watts has a frequency range of 3-20 m/s. 2. The troo-stage signalling. 3. The remainiter is an e-circuit succenteration with the solutional distress signalling. 4. The ship of tensor transmitter has a frequency range of 2.5 to 30 m/s incorporating a selector for 5/0 ke's and an automatic claras signals of the structure. 4. For ship to ship traffic there is a radio of about 125 me's incorporating a receiver with a direction-dimining entenum. 50X1-HUM 50	MBJECT			NO. OF PAGES 2 50X1-HUM		
THIS IS UNEVALUATED INFORMATION 1. The Ministry of Industry has been given the took of furnishing the new East German fiching fleet and cosan-young reparations ships with the following specially—leveloped equipment 3. Two-stage transmitter with 80-watt peak power output, 1/T* and 8/T. 2. The two-stage 20-watt wannitters for occan-going ships and 20-watt ship to ship communication, R/T. 2. The two-stage 20-watt transmitter for occan-going ships and 20-watt the new East German fishing fleet. It has a frequency of 1.5 to 3.5 mc's and the accompanying receiver is a seven-circuit superheterodyne. The supply is 24 volts over two transformers. 3. The two-stage 20-watt transmitter is a W/T and R/T transmitter for pack power transmissions of shout 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The shinal transmitter said ship to ship communications equipment are described as follows: a. The transmitter with a pask power of 200 watts has a frequency range of 3-70 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's 125 kc's, with automatic distress signalling. c. The receiver is an 2-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-Cinding outoma. e. All of this equipment is fed by an AC of 220 volts.				(FISTED BELOW)		
THIS IS UNEVALUATED INFORMATION 1. The Ministry of Industry has been given the tack of furnishing the new matter an extraction as a second control of the				SUPPLEMENT TO		
1. The Ministry of Industry has been given the tack of furnishing the new Kast German flahing fleet and ocean-going repurations ships with the following specially-developed equipment a. Two-stage transmitter with 80-watt peak power output, 1/7% and R/T. c. 200- and 100-watt W/T transmitters for ocean-going ships and 20-watt ship to ship communication, R/T. 2. The two-stage 20-watt transmitter is developed for R/T communication with the new Rast German fishing fleet. It has a frequency of 1.5 to 3.5 no's and the accompanying receiver is a seven-circuit superheterodyne. The supply is 2% volts over two transformers. 3. The two-stage 80-watt transmitter is a W/T and R/T transmitter for peak power transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The ships' transmitters and ship to ship communications equipment are described as follows: a. The transmitter with s peak power of 200 watte has a frequency range of 3-20 no's. b. The 100-watt transmitter has a frequency range of 500 ke's a 15 ke's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 me's incorporating a selector for 500 ke's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 me's incorporating a receiver with a direction-finding entenna. e. All of this equipment is fed by an AC of 220 volts.	THE BOOKSBURT	Constant Constant System	is opening the article of the rational devided.			
East German fishing fleet and ocean-going reparations ships with the following specially-developed equipment a. Two-stage transmitter. 20-watt. R/T.* b. Two-stage transmitter with 80-watt peak power output, W/T* and R/T. c. 200- and 100-watt W/T transmitters for ocean-going ships and 20-watt ship to ship communication, R/T. The two-stage 20-watt transmitter is developed for R/T communication with the new East German fishing fleet. It has a frequency of 1.5 to 3.5 mc's and the accompanying receiver is a seven-circuit superheterodyne. The supply is 2k volts over two transformers. The two-stage 80-watt transmitter is a W/T and R/T transmitter for peak power transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. The ships' transmitters and ship to ship communications equipment are described as follows: a. The transmitter with a peak power of 200 watts has a frequency range of 3-20 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's ± 15 kc's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding antenna. e. All of this equipment is fed by an AC of 220 volts.	a de la	er. (.) a d in any . Repodi	ORCHOR OF ANY RENEW IS ESCHIPTING.	IS UNEVALUATED INFORMATION 50X1-HUM		
 a. Two-stage transmitter, 20-watt, R/T.* b. Two-stage transmitter with 80-watt peak power output, U/T* and R/T. c. 200- and 100-watt W/T transmitters for occen-going ships and 20-watt ship to ship communication, R/T. 2. The two-stage 20-watt transmitter is developed for R/T communication with the new Rast Gernan fishing fleet. It has a frequency of 1.5 to 3.5 mc's and the accompanying receiver is a seven-circuit superheterodyne. The supply is 2k volts over two transformers. 3. The two-stage 80-watt transmitter is a W/T and R/T transmitter for peak power transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The ships' transmitters and ship to ship communications equipment are described as follows: a. The transmitter with a peak power of 200 watts has a frequency range of 3-20 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's - 15 kc's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding automa. e. All of this equipment is fed by an AC of 220 volts. 	1.`	Eas	st German fishing fleet and ocean-going re	eparations ships with the follow-		
the new East German fishing fleet. It has a frequency of 1.5 to 3.5 me's and the accompanying receiver is a seven-circuit superheterodyne. The supply is 2k volts over two transformers. 3. The two-stage 80-watt transmitter is a W/T and R/T transmitter for peak power transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The ships' transmitters and ship to ship communications equipment are described as follows: a. The transmitter with a peak power of 200 watts has a frequency range of 3-20 me's. b. The 100-watt transmitter has a frequency range of 500 ke's g 15 ke's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 me's incorporating a selector for 500 ke's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 me's incorporating a receiver with a direction-finding antonna. e. All of this equipment is fed by an AC of 220 volts.		a. b.	Two-stage transmitter, 20-watt, R/T,* Two-stage transmitter with 80-watt peak 200- and 100-watt W/T transmitters for or	power output, W/T* and R/T.		
transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate frequency oscillator. 4. The ships' transmitters and ship to ship communications equipment are described as follows: a. The transmitter with a peak power of 200 watts has a frequency range of 3-20 nc/s. b. The 100-watt transmitter has a frequency range of 500 kc/s * 15 hc/s, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc/s incorporating a selector for 500 kc/s and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc/s incorporating a receiver with a direction-finding antenna. e. All of this equipment is fed by an AC of 220 volts.	2.	the and	the new East German fishing fleet. It has a frequency of 1.5 to 3.5 mc's and the accompanying receiver is a seven-circuit superheterodyne. The			
 a. The transmitter with a peak power of 200 watts has a frequency range of 3-20 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's ± 15 kc's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding antenna. e. All of this equipment is fed by an AC of 220 volts. 	3. •	tra: in	transmissions of about 80 watts. The whole is similar to the one described in paragraph 2 above except that the receiver has an additional intermediate			
 3-20 mc's. b. The 100-watt transmitter has a frequency range of 500 kc's + 15 kc's, with automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding antenna. e. All of this equipment is fed by an AC of 220 volts. 	Å.					
automatic distress signalling. c. The receiver is an 8-circuit superheterodyne with a frequency range of 1.5 to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding antonna. e. All of this equipment is fed by an AC of 220 volts.						
to 30 mc's incorporating a selector for 500 kc's and an automatic alarm signals activator. d. For ship to ship traffic there is a radio of about 125 mc's incorporating a receiver with a direction-finding antenna. e. All of this equipment is fed by an AC of 220 volts.		Ď,				
e. All of this equipment is fed by an AC of 220 volts.		C,	to 30 mc's incorporating a selector for 500 kc's and an automatic alarm			
		á.				
CLASSIFICATION _SPECIAL/COUTROL _ U.S. OFFICIALS ONLY		e.	All of this equipment is fed by an AC of	220 volts.		
STATE X HAVY X NSR3 DISTRIBUTION						

1 11 JUL 1978

50X1-HUM

SECHET/CONTROL - U.S. OFFICIALS ONLY

CENTRAL INTELLIGENCE AGENCY

50X1-HUM

- 2 - CONFIDENTIAN

In addition to the above equipment, former German ships now being refitted in Baltic ports under the supervision of Col. Litvinov, of the SKK's Scientific and Technological Department (Soviet Navy), Karlshorst, are receiving W/T. They are the following:

ASIA:

200-watt Ehrenmal transmitter with a frequency range of 3-23 mc's and a 500-watt Ehrenmal transmitter with a frequency range of 350 to 600 kc's. The associated receivers are Siemens All-Wave.

ILYA REPIN:

A 200-watt Ehrenmal transmitter for this ship is

still lying on the quay at Wismar.

NACHIMOD**) HANSA RUSS PRIMORYE

500-watt and 800-watt Ehrenmal transmitters have been delivered to each of these four ships.

GORCH FOCK:

A Torenz Lo 40 K 39 transmitter is to be installed.

The first sixty of a number of marine transmitters of the Lorenz Ehrenmal Lo 800 FKW type have been delivered to the USSR.

Comment: R/T presumably means clear or voice transmission, while W/T is presumably code or key transmission.

50X1-HUM

Comment: This may possibly be NAKHIMOV, a name which is fairly

50X1-HUM

common in Russian naval matters.

CONFIDENTIAL